

IBM Cúram Social Program Management
Version 7.0.3

*Cúram Priority, Complexity, Risk
Configuration Guide*



Note

Before using this information and the product it supports, read the information in [“Notices” on page 7](#)

Edition

This edition applies to IBM® Cúram Social Program Management v7.0.3 and to all subsequent releases unless otherwise indicated in new editions.

Licensed Materials - Property of IBM.

© **Copyright International Business Machines Corporation 2012, 2018.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

© .

Contents

List of Tables.....	iv
Chapter 1. Configuring Priority, Complexity, Risk Processing.....	1
Introduction.....	1
Purpose.....	1
Audience.....	1
Selected Reading.....	1
Chapters in this Guide.....	1
Creating a PCR Configuration.....	2
Introduction.....	2
Basic Configuration Details.....	2
Selecting a PCR Rule Set.....	2
Associating a PCR Configuration with a Case.....	2
Deferred Processing.....	2
Running a PCR Assessment.....	3
Manually Entering a PCR Assessment.....	3
Automatically Running a PCR Assessment.....	3
PCR Configuration Lifecycle.....	3
Configuring PCR Range Mappings.....	3
Introduction.....	3
Range Mapping Settings.....	3
Configuring a PCR Rule Set.....	4
Introduction.....	4
Configuring a PCR Rule Set.....	4
Mandatory Rule Attributes.....	4
Specifying Rule Set Properties Text.....	6
Notices.....	7
Privacy Policy considerations.....	8
Trademarks.....	8

List of Tables

- 1. Selected Reading.....1
- 2. Basic Configuration Details for PCR..... 2
- 3. PCR Range Mapping Settings..... 4
- 4. Mandatory Rule Attributes for PCR Rule Sets.....5

Chapter 1. Configuring Priority, Complexity, Risk Processing

You can configure priority complexity risk processing. Ratings can be triggered to be calculated automatically or entered manually by a case worker. Ratings are calculated from rule sets, which are recorded by administrators for each priority complexity risk configuration.

Introduction

Purpose

The purpose of this guide is to describe the configuration options available for Priority, Complexity, Risk (PCR) processing. PCR processing allows the worker to calculate the priority, complexity and risk ratings for a case. PCR ratings can be triggered to be calculated automatically or entered manually by a case worker. Automatic PCR ratings are calculated using rule sets which are recorded by administrators for each PCR configuration. PCR must be configured before it can be used to determine the PCR rating for a case.

Audience

This guide is intended for administrators responsible for configuring the PCR component. It is assumed that the administrators have worked with code tables as part of Cúram system administration.

For PCR rule set configuration, previous knowledge of Cúram Express Rules is required.

Selected Reading

Table 1: Selected Reading	
Document Name	Description
Cúram Common Intake Guide	This document provides a detailed overview of Cúram Common Intake functionality including PCR.
Working with Cúram Express Rules	This provides step by step instructions on how to create Cúram Express Rule sets and how to use the Cúram Express Rules Editor to add business and technical logic to a rule set.
Cúram Express Rules Reference Manual	This provides detailed information on the Cúram Express Rules language, development environment and run-time features.

Chapters in this Guide

The following chapters are included in this guide:

Creating a PCR Configuration

This chapter describes how PCR is configured.

Configuring PCR Range Mappings

This chapter describes how to configure PCR range mappings.

Creating a PCR Rule Set

This chapter describes how to create a PCR rule set.

Creating a PCR Configuration

Introduction

This chapter provides information on the different settings available when creating a PCR configuration. The following areas of PCR configuration are covered:

- Basic PCR configuration details
- PCR Rule Set Selection
- Associating a PCR configuration with a case
- Deferred processing
- Running a PCR assessment
- Manually entering a PCR assessment

Basic Configuration Details

<i>Table 2: Basic Configuration Details for PCR.</i> This table describes the basic configuration details for a PCR assessment	
Item	Description
Name	Mandatory text field. Individual PCR configurations can share the same name. For example, a PCR configuration called MyCaseConfiguration has a date range of January 1st - March 1st. A second configuration with the same name starting on March 2nd for the same case is also possible, because you may not want to rename the configuration.
Start Date	Mandatory field. Date when the PCR configuration starts.
End Date	Not Mandatory. Date when the PCR configuration ends. If no end date is specified the PCR configuration is considered to apply indefinitely from the start date.

Selecting a PCR Rule Set

A PCR rule set which is used to calculate the PCR ratings for the case can be selected for a PCR configuration. This PCR rule set must be valid. For more information, see [“Configuring a PCR Rule Set” on page 4.](#)

Associating a PCR Configuration with a Case

PCR configurations must be associated with a case type. The case type can be selected from the dropdown list.

Deferred Processing

PCR calculation can be deferred to off peak times ensuring that PCR calculations do not cut into performance overhead. Selecting the Deferred Processing checkbox will calculate the PCR rating in deferred processing mode. Note that this setting is also not directly used in PCR processing OOTB.

Running a PCR Assessment

The 'Assess PCR' option, when configured, allows the case worker to manually run a PCR assessment. This results in the execution of the PCR rules which calculate the rating.

Manually Entering a PCR Assessment

Case workers can manually enter a PCR assessment without the use of a rule set. The 'Enter PCR' option is displayed when the organization has configured to allow the user to manually enter the PCR classification for the case. The functionality is enabled via a checkbox during PCR configuration. Once configured, the caseworker will see a button on the PCR tab which brings them to a modal page where they can enter a manual PCR assessment. For more information, see the *Cúram Common Intake Guide*.

Automatically Running a PCR Assessment

PCR run points determine when the PCR rules are executed for the automatic determination of PCR ratings. A PCR run point is a point at which the PCR rule set can be triggered to run and calculate the PCR rating for a case. Most of these points require a particular event to be raised in order to trigger the PCR assessment. For example, a point called 'Application Submitted' is available which can be used to allow a case worker to automatically assess PCR when an application is submitted. When the application is submitted, the run point is verified, and the PCR assessment is run.

The sample run points provided for automatic PCR calculation are as follows:

- Evidence Applied
- Add Program Application
- Confirm Withdraw Program Application
- Check Eligibility
- Application Submitted
- Remove Applicant
- Add Registered Client

Note: An event is not raised when a manual PCR assessment is entered.

PCR Configuration Lifecycle

When a PCR configuration is first created it has a status of unpublished. An unpublished PCR configuration cannot be used in calculating PCR.

PCR configurations can be used for PCR calculations once they are published. It is not possible to publish a PCR configuration if there is another PCR configuration for the same case type with overlapping dates. Range mappings must be defined before publishing a PCR configuration. Modifying a published PCR configuration will return the configuration to unpublished.

Configuring PCR Range Mappings

Introduction

This chapter provides information on the different settings available when creating a PCR range mapping. Range mappings must be defined for each of the PCR ratings. Range mappings provide a textual classification for ranges of numbers for each rating. For example, a priority range mapping could be defined from 0 – 50 with a classification of 'low'. If the rule set calculates a priority rating of 20 this is displayed to the user as a low priority.

Range Mapping Settings

Table 3: PCR Range Mapping Settings.

This table describes PCR range mapping settings

Type	Description
Type	Mandatory field. The PCR range mapping type is a dropdown list containing priority, complexity and risk entries. This dropdown list is based on the PCRTYPE codetable.
Classification	Mandatory field. The PCR classification is a dropdown for selecting the text to associate with the range. The dropdown is based on the PCRclassification codetable.
Range Start	Mandatory field. The range start is the value from which this range comes into effect.
Range End	Range end is the last value at which this range applies. If the range end is blank then the range applies indefinitely from the range start date. Ranges cannot overlap within a type and each classification can only be defined once per type.

Configuring a PCR Rule Set

Introduction

This chapter provides an overview of the PCR rule set structure and details how a customer can create a PCR rule set. PCR rule sets are used to calculate a result for the priority, complexity, and risk rating for a case scenario. Each of the components which make up a PCR assessment is represented as an attribute in the PCR rule set. A rule can have an associated weighting which is added to the overall PCR calculation if it succeeds. The rules then determine the overall rating and classification of the case.

Configuring a PCR Rule Set

Each PCR Rule Set must contain a rule class which inherits from the AbstractPCR class. This rule class is the class which produces the PCR results to be displayed to the worker.

To create a PCR rule class, first create the rule class using the CER editor, naming the rule class appropriately.

The usage of the PCRRuleSet rule class guarantees that the required attributes are available during rules execution. For more information on setting up rule sets, see the *Cúram Express Rules Cookbook*.

A PCR rule set must inherit from the PCRRuleSet and provide an implementation for each of the six abstract attribute within the defined rule set. The description attribute is inherited from the root rule class and each solution must also provide its own implementation of this attribute.

Mandatory Rule Attributes

Table 4: Mandatory Rule Attributes for PCR Rule Sets.

This table describes mandatory rule attributes to be used for PCR rule sets

Rule Attribute	Type	Purpose
caseID	Number	Specified case identifier attribute for which the PCR rules execution relates to.
description	String	This attributes represents the text defining the property description. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
priorityRate	Number	This attribute is a calculated attribute representing the relative ranking of the case against a baseline to determine a timeline for response.
priorityReason	String	This attribute represents the text defining the property priority reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
complexityRate	Number	This attribute is a calculated attribute representing the ranking of a case against a baseline to determine the resource(s) required for a response.
complexityReason	String	This attributes represents the text defining the property complexity reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
riskRate	Number	This attribute is a calculated attribute representing the relative ranking of a case against a baseline to determine its potential impact to the agency.
riskReason	String	This attributes represents the text defining the property risk reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.

Specifying Rule Set Properties Text

The rule set properties text is specified by creating an entry in a localized property file as follows:

- Create a property file, for example, PCRSample.properties.
- Add each entry to the property file that will be referenced by the Rule Class attributes. The value of each of these entries is the localized text to be displayed in the application. The following example outlines an example property entry in a PCRSample.properties file and how the property is referenced by a rule set attribute:

```
# This Properties file contains resource
strings for the Sample PCR Rule set.
PCRSample.description=PCRSample
PCRSample.samplePriorityReason=Sample Priority Reason

<Attribute name="description">
  <type>
    <javaclass name="curam.creole.value.Message"/>
  </type>
  <derivation>
    <ResourceMessage
      key="PCRSample.description"
      resourceBundle="curam.pcrsample.rules.PCRSample"
    >
  </ResourceMessage>
</derivation>
</Attribute>
```

- Add the Properties file entry to the Resource Store by updating the 'Dynamic UIM' section of the Administration Application. In the above example, this entails adding a PCRSample.properties entry in the Dynamic UIM section of the administration application, along with a corresponding page ID, a resource store category, and a properties file.

Notices

This information was developed for products and services offered in the United States.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing Legal and Intellectual Property Law IBM Japan Ltd. 19-21, Nihonbashi-Hakozakicho, Chuo-ku Tokyo 103-8510, Japan

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

All IBM prices shown are IBM's suggested retail prices, are current and are subject to change without notice. Dealer prices may vary.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Privacy Policy considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies or other similar technologies that collect each user's name, user name, password, and/or other personally identifiable information for purposes of session management, authentication, enhanced user usability, single sign-on configuration and/or other usage tracking and/or functional purposes. These cookies or other similar technologies cannot be disabled.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Trademarks

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/copytrade.shtml>.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java™ and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other names may be trademarks of their respective owners. Other company, product, and service names may be trademarks or service marks of others.



Part Number:

(1P) P/N: