

IBM Cúram Social Program Management
Version 7.0.3

*Cúram Evidence Generator Modeling
Guide*



Note

Before using this information and the product it supports, read the information in [“Notices” on page 9](#)

Edition

This edition applies to IBM® Cúram Social Program Management v7.0.3 and to all subsequent releases unless otherwise indicated in new editions.

Licensed Materials - Property of IBM.

© **Copyright International Business Machines Corporation 2012, 2018.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

© .

Contents

List of Tables.....	iv
Chapter 1. Modeling for the Evidence Generator.....	1
Introduction.....	1
Purpose.....	1
Prerequisites.....	1
Audience.....	1
Entity Modeling.....	1
Entity.....	1
Required Structs.....	2
Build Process.....	3
Parent / Child Relationships.....	4
Introduction.....	4
Additional Aggregations.....	4
Multiple Mandatory Parent Relationships.....	4
Introduction.....	4
Additional Aggregations.....	4
Pre Association Relationships.....	5
Introduction.....	5
Additional Aggregations.....	5
Case Participant Attributes.....	5
Introduction.....	5
Additional Aggregations.....	5
Additional Case Participant Attributes.....	6
Related Entity Attributes.....	6
Introduction.....	7
Additional Structs.....	7
Additional Aggregations.....	7
Non Evidence Attributes.....	7
Introduction.....	7
Additional Structs Required.....	7
Additional Aggregations.....	7
Non Modifiable Entities.....	8
Introduction.....	8
Additional Aggregations.....	8
Notices.....	9
Privacy Policy considerations.....	10
Trademarks.....	10

List of Tables

1. Required Aggregations..... 3

2. Required Aggregations..... 3

3. Additonal Aggregations..... 4

4. Additonal Aggregations..... 4

5. Additonal Aggregations..... 5

6. Additonal Aggregations..... 5

7. Additonal Aggregations..... 5

8. Additonal Aggregations..... 6

9. Additonal Aggregations..... 6

10. Additonal Aggregations..... 6

11. Additonal Aggregations..... 7

12. Additonal Aggregations..... 7

13. Additonal Aggregations..... 8

14. Additonal Aggregations..... 8

Chapter 1. Modeling for the Evidence Generator

Use this information to learn about entity modeling that is required to use the Cúram evidence generator. The evidence generator relies on the existence of certain attributes, structs, and aggregations within the generated code. Various modeling strategies are required for the different metadata patterns available in the generator.

Introduction

Purpose

The purpose of this document is to outline the entity modelling required when using the Cúram Evidence Generator, as it relies on the existence of certain attributes, structs and aggregations within the generated code.

Starting with the basic modelling required for all entities, the guide will then outline any additional modelling required for the different metadata patterns available in the generator.

Prerequisites

In order to model the structs, the reader should

- Be familiar with the Cúram Server Modeling Guide
- Have read the Designing Cúram Evidence Solutions Guide
- Have read the Cúram Evidence Developers Guide

Audience

This guide is targeted at those developers intending to make use of the Cúram Evidence Generator.

Entity Modeling

Entity

The entity is the starting point of development for any engineer. Details of how to model an entity are outlined in the Cúram Server Modeling Guide.

In addition to the normal entity modelling, the following settings are required in order that it can work correctly with the generated code.

Code Package

The Code Package for the Entity and all its associated structs must be specified in the model, for example:

```
CODE_PACKAGE=seg.evidence.entity
```

Note: The code package must correspond with the `product.ejb.package` property (see Cúram Evidence Generator Cookbook, section 8.2)

Optimistic Locking

Optimistic locking must be switched on at the entity level. This is because the evidence solution, which will be interacting with the entity, relies on database controlled versioning.

Required Attributes

The evidence generator relies on the existence of certain attributes to execute successfully.

Key Field

The key field of the entity must be named *evidenceID*. The rationale for this is that it results in a lot less generated entity key structs on the server side.

Required Operations

The evidence generator relies on the existence of certain operations to execute successfully.

insert

The insert operation should use the stereotype insert.

Auto ID

The Auto ID setting should be turned on for the *evidenceID* so as to generate the unique identifier for the insertion of records onto the database. The evidence generator assumes that this is turned on.

Pre Data Access Operation

This option should be set to Yes

modify

The modify operation should use the stereotype modify.

Pre Data Access Operation

This option should be set to Yes

Optimistic Locking

This option should be set to Yes

read

The read operation should use the stereotype read.

remove

The remove operation should use the stereotype remove.

Customizing an Out-Of-The-Box Evidence Entity

Customizing an out-of-the-box evidence entity involves creating an entity extension in the custom model as described in the *Cúram Server Modeling Guide*.

Code Package

The code package for the extension must be specified in the model, for example:

```
CODE_PACKAGE=custom.seg.evidence.entity
```

Note: The code package must correspond with the `product.ejb.package` property (see *Cúram Evidence Generator Cookbook*, section 8.2) that is configured in the out-of-the-box product, prepended with the text `custom.`, as above.

Required Structs

Rather than creating similar / identical structs at each layer, the evidence generator uses the structs created at the entity layer to pass data through to the façade layer. For this reason it is important for the generator that certain structs are created and named with the correct naming convention. It should also

be noted that additional aggregations will be required under certain conditions. These conditions are explained in detail in the next section.

<EntityName>EvidenceDetails

A struct named <EntityName>EvidenceDetails must be created. This struct must have no attributes of its own, and must include the following aggregations:

Table 1: Required Aggregations		
Object	Aggregation Name	Multiplicity
The entity being modeled	dtls	1:1
core.sl.EvidenceDescriptorDetails	descriptor	1:1
core.sl.CaseIDKey	caseIDKey	1:1

Read<EntityName>EvidenceDetails

A struct named Read<EntityName>EvidenceDetails must be created. This struct must have no attributes of its own, and must include the following aggregations:

Table 2: Required Aggregations		
Object	Aggregation Name	Multiplicity
The entity being modeled	dtls	1:1
core.sl.EvidenceDescriptorDetails	descriptor	1:1

Build Process

The reason no additional modeling is required beyond the entity layer is that the evidence generator infers the classes required at service and façade layer. The reason that this is possible is that:

- the evidence solution provides the necessary tools for maintaining evidence records
- the evidence generator uses a combination of the structs that have been created at the entity layer by the developer and a number of structs which are provided by the evidence solution

Service Layer

During the build the generator creates a process class for each evidence entity at the service layer level. The process class created has at least the following operations

- create<Entity Name>
- read<Entity Name>
- modify<Entity Name>

There may be more functions created to deal with some of more specialized scenarios but these are generated without the developer's knowledge and the implemented code required to execute these functions is also generated by the evidence generator.

Façade Layer

At the façade layer the evidence generator generates a single process class per product which contains all of the functions required for evidence maintenance. For each single entity at least the following functions are added to this process class:

- create<Entity Name>Evidence
- read<Entity Name>Evidence

- modify<Entity Name>Evidence

Similar to the service layer, there may be additional functions created to deal with some of the more specialized scenarios but again these will not require any input from the developer.

Note: No list<Entity Name>Evidence function is listed above as the generic listEvidence function on the Evidence facade is used instead. This also accounts for no list<Entity Name> function on the Service Layer.

Parent / Child Relationships

Introduction

If an evidence entity is taking the role of a child in a Parent / Child relationship the following additional aggregations must be specified

Additional Aggregations

<EntityName>EvidenceDetails

This struct must now also aggregate the following structs:

Table 3: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.EvidenceKey	parEvKey	1:1
core.sl.ParentSelectDetails	selectedParent	1:1

Multiple Mandatory Parent Relationships

Introduction

If an evidence entity is taking the role of a child with multiple mandatory parents, the following additional aggregations must be specified

Additional Aggregations

<EntityName>EvidenceDetails

This struct must now also aggregate the following struct for each of the mandatory parent types:

Table 4: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.EvidenceKey	<Parent Entity Name>ParEvKey	1:1

Note: It should be noted that the first letter of the above aggregation name should be lowercase, in keeping with standard Java™ naming practices

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following struct for each of the mandatory parent types:

Table 5: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.ParentEvidenceLink	<Parent Entity Name>ParentEvidenceLink	1:1

Note: It should be noted that the first letter of the above aggregation name should be lowercase, in keeping with standard Java naming practices

Pre Association Relationships

Introduction

If the developer requires the use of the PreAssociation pattern then the following additional modeling is required.

Additional Aggregations

<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 6: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.EvidenceKey	preAssocKey	1:1

Case Participant Attributes

Introduction

If adding a case participant attribute to the entity, some further aggregations are required to allow the details be added correctly

Additional Aggregations

<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 7: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.CaseParticipantDetails	caseParticipantDetails	1:1

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 8: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.ReadCaseParticipantDetailss	caseParticipantDetails	1:1

Additional Case Participant Attributes

In certain circumstances it might be a business requirement to have a case participant, other than the primary case participant, stored as a piece of evidence data. A simple example of this would be for a piece of evidence named 'Medical Report'. Not only is it necessary to store the ID of the person for whom the medical report was commissioned, it's also necessary to store the ID of the medical practitioner who compiled the report. Other examples of case participants might be Education Faculties, Unions or Employers.

As the above scenario has in the past caused difficulties for developers, a new feature now exists which allows a developer to flag an attribute, via metadata, as being a special 'case participant' attribute. This means that this attribute will store the role ID of the case participant. The developer must provide the name attribute in the CaseParticipant element of the EUIM metadata, and use this name when aggregating the structs.

Additional Aggregations

In order to facilitate the generator in its handling of this special flag, the two required structs must aggregate some additional structs.

<EntityName>EvidenceDetails

This struct must now also aggregate the following structs:

Table 9: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.CaseParticipantDetails	<name>CaseParticipant Details	1:1

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following structs:

Table 10: Additional Aggregations		
Object	Aggregation Name	Multiplicity
core.sl.ReadCaseParticipantDetails	<name>CaseParticipant Details	1:1

Related Entity Attributes

Introduction

In certain circumstances it might be a business requirement to have a field value from a related entity available either for display or for use when maintaining an entity. This can act as a helpful hint for users, when entering information.

Typically the information used would be from a parent evidence record.

For example, displaying the remaining unallocated amount of an income record, when attempting to allocate this income against expenses.

Additional Structs

In a scenario similar to this, an additional struct must be created at the entity layer to hold the related information.

<EntityName>RelatedEntityAttributesDetails

This struct must have as attributes any attribute to be shared between the entities and this attribute must be of the appropriate type.

Additional Aggregations

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following structs:

Table 11: Additional Aggregations		
Object	Aggregation Name	Multiplicity
<EntityName>RelatedEntityAttributesDetails	relatedEntityAttributes	1:1

Non Evidence Attributes

Introduction

If an entity is using the Non Evidence Details pattern, an extra struct must be modeled and aggregated into the standard evidence structs

Additional Structs Required

<EntityName>NonEvidenceDetails

This struct must be modeled and hold all the extra attributes required for this entity.

Additional Aggregations

<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 12: Additional Aggregations		
Object	Aggregation Name	Multiplicity
<EntityName>NonEvidenceDetails	nonEvidenceDetails	1:1

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 13: Additonal Aggregations		
Object	Aggregation Name	Multiplicity
<EntityName>NonEvidenceDetails	nonEvidenceDetails	1:1

Non Modifiable Entities

Introduction

If the developer requires that the entity should not be modifiable then additional modeling is required.

Additional Aggregations

Read<EntityName>EvidenceDetails

This struct must now also aggregate the following struct:

Table 14: Additonal Aggregations		
Object	Aggregation Name	Multiplicity
curam.core.sl.infrastructure.struct.ECWarningsDtls List	warnings	1:1

Notices

This information was developed for products and services offered in the United States.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information on the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

For license inquiries regarding double-byte character set (DBCS) information, contact the IBM Intellectual Property Department in your country or send inquiries, in writing, to:

Intellectual Property Licensing Legal and Intellectual Property Law IBM Japan Ltd. 19-21, Nihonbashi-Hakozakicho, Chuo-ku Tokyo 103-8510, Japan

INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

Any references in this information to non-IBM websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those websites are not part of the materials for this IBM product and use of those websites is at your own risk.

IBM may use or distribute any of the information you provide in any way it believes appropriate without incurring any obligation to you.

Licensees of this program who wish to have information about it for the purpose of enabling: (i) the exchange of information between independently created programs and other programs (including this one) and (ii) the mutual use of the information which has been exchanged, should contact:

IBM Director of Licensing IBM Corporation North Castle Drive, MD-NC119 Armonk, NY 10504-1785 US

Such information may be available, subject to appropriate terms and conditions, including in some cases, payment of a fee.

The licensed program described in this document and all licensed material available for it are provided by IBM under terms of the IBM Customer Agreement, IBM International Program License Agreement or any equivalent agreement between us.

The performance data and client examples cited are presented for illustrative purposes only. Actual performance results may vary depending on specific configurations and operating conditions.

Information concerning non-IBM products was obtained from the suppliers of those products, their published announcements or other publicly available sources. IBM has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

Statements regarding IBM's future direction or intent are subject to change or withdrawal without notice, and represent goals and objectives only.

All IBM prices shown are IBM's suggested retail prices, are current and are subject to change without notice. Dealer prices may vary.

This information is for planning purposes only. The information herein is subject to change before the products described become available.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

COPYRIGHT LICENSE:

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to IBM, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. IBM, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. IBM shall not be liable for any damages arising out of your use of the sample programs.

Privacy Policy considerations

IBM Software products, including software as a service solutions, ("Software Offerings") may use cookies or other technologies to collect product usage information, to help improve the end user experience, to tailor interactions with the end user or for other purposes. In many cases no personally identifiable information is collected by the Software Offerings. Some of our Software Offerings can help enable you to collect personally identifiable information. If this Software Offering uses cookies to collect personally identifiable information, specific information about this offering's use of cookies is set forth below.

Depending upon the configurations deployed, this Software Offering may use session cookies or other similar technologies that collect each user's name, user name, password, and/or other personally identifiable information for purposes of session management, authentication, enhanced user usability, single sign-on configuration and/or other usage tracking and/or functional purposes. These cookies or other similar technologies cannot be disabled.

If the configurations deployed for this Software Offering provide you as customer the ability to collect personally identifiable information from end users via cookies and other technologies, you should seek your own legal advice about any laws applicable to such data collection, including any requirements for notice and consent.

For more information about the use of various technologies, including cookies, for these purposes, see IBM's Privacy Policy at <http://www.ibm.com/privacy> and IBM's Online Privacy Statement at <http://www.ibm.com/privacy/details> the section entitled "Cookies, Web Beacons and Other Technologies" and the "IBM Software Products and Software-as-a-Service Privacy Statement" at <http://www.ibm.com/software/info/product-privacy>.

Trademarks

IBM, the IBM logo, and [ibm.com](http://www.ibm.com) are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at <http://www.ibm.com/legal/copytrade.shtml>.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

Linux is a registered trademark of Linus Torvalds in the United States, other countries, or both.

Microsoft, Windows, Windows NT, and the Windows logo are trademarks of Microsoft Corporation in the United States, other countries, or both.

UNIX is a registered trademark of The Open Group in the United States and other countries.

Other names may be trademarks of their respective owners. Other company, product, and service names may be trademarks or service marks of others.



Part Number:

(1P) P/N: